Turbosound processor library list

TXD and TCS series					
Note: Gain structure will change depending on configuration.					
Model	**File name**	**Mode**	**Module**		**Driver**
TXD Passive top with TXD bass	**TXD_pa_w_bass**	Passive	1way		8/12/15"+1"
TXD Bass	**TXD_bass**	Sub	1way		15"/ 18"
TXD-252 Biamp	**TXD252_bi**	Biamp	2way	Hi	1.4"
				Low	2 x 15"
TXD-252 Biamp + TXD-218	**TXD252_bi+TXD218**	Biamp+Sub	3way	Hi	1.4"
				Mid	2 x 15"
				Low	2 x 18"
TCS Passive top with TCS bass	**TCS_pa_w_bass**	Passive	1way		8/1012/15"+1"
TCS bass	**TCS_bass**	Sub	1way		15"/ 18"
TQ-400 Series					
Model	**File name**	**Mode**	**Module**		**Driver**
TQ-445 Full Range	**TQ445_bi**	Biamp	2way	Hi	6.5" + 1"
				Low	12"
TQ-445 + TQ-425	**TQ445_bi+TQ425**	Biamp+Sub	3way	Hi	6.5" + 1"
				Mid	12"
				Low	2 x 15"
TQ-445 + TSW-718	**TQ445_bi+TSW718**	Biamp+Sub	3way	Hi	6.5" + 1"
				Mid	12"
				Low	2 x 18"
ASPECT (TA-800) series					
Note: Gain structue will change dramatically depending on system size, this is based on an 9 per side indoor system. Consult Aspect manual or Turbosound for additional information.					
Settings are based on 26dB gain amplifiers.					
Model	**File name**	**Mode**	**Module**		**Driver**
TA-800 4 way v.2 flare 2 x 15" bass	**TA800+15_4wy**	Triamp+Sub	4way	Hi	2 x 50mm
				Hi-Mid	10"
				Low-Mid	2 x 10"
				Low	2 x 15"
TA-800 5 way v.2 flare	**TA800+15+18_5wy**	Triamp+Sub+Sub	5way	Hi	2 x 50mm
				Hi-Mid	10"
				Low-Mid	2 x 10"
				Low	2 x 15"
				Sub-Low	2 x 18"
TA-800 4 way v.2 flare with TSW218	**TA800+TSW218_4wy**	Triamp+Sub	4way	Hi	2 x 50mm
				Hi-Mid	10"
				Low-Mid	2 x 10"
				Low	2 x 18"
Aspect Wide (TA-500) series					
Model	**File name**	**Mode**	**Module**		**Driver**
TA-500 Full range 3 way (Bi-Amp)	**TA500_bi**	Biamp	2way	Hi	10" + 50mm
				Low	15"
TA-500 + B-18 4 way (Tri-Amp)	**TA500_bi+B18**	Biamp+Sub	3way	Hi	10" + 50mm
				Mid	15"
				Low	1 x 18"
TA-500 + TSW-218 4 way (Tri-Amp)	**TA500_bi+TSW218**	Biamp+Sub	3way	Hi	10" + 50mm
				Mid	15"
				Low	2 x 18"
TA-500 Full range 3 way	**TA500_tri**	Triamp	3way	Hi	1 x 50mm
				Mid	10"
				Low	15"
TA-500 + 2 x B-18 4 way	**TA500_tri+B18**	Triamp+Sub	4way	Hi	1 x 50mm
				Hi-Mid	10"
				Low-Mid	15"
				Low	1 x 18"
TA-500 + TSW-218 4 way	**TA500_tri+TSW218**	Triamp+Sub	4way	Hi	1 x 50mm
				Hi-Mid	10"
				Low-Mid	15"
				Low	2 x 18"
TFM series					
Model	**File name**	**Mode**	**Module**		**Driver**
TFM-420	**TFM420_bi**	Biamp	2way	Hi	2"
				Low	12"
TFM-450	**TFM450_bi**	Biamp	2way	Hi	2"
				Low	15"
TFM-350	**TFM350_bi**	Biamp	2way	Hi	2"
				Low	15"

NuQ series					
Model	**File name**	**Mode**	**Module**		**Driver**
NuQ 8	**NuQ8**	Passive	1way		8" + 1"
NuQ 8 + B15	**NuQ8+B15**	Passive+Sub	2way	Hi	8" + 1"
				Low	15"
NuQ 10	**NuQ10**	Passive	1way		10" + 1"
NuQ 10 + B15	**NuQ10+B15**	Passive+Sub	2way	Hi	10" + 1"
				Low	15"
NuQ 12 Passive	**NuQ12_pa**	Passive	1way		12" + 1.4"
NuQ 12 Passive + B18	**NuQ12_pa+B18**	Passive+Sub	2way	Hi	12" + 1.4"
				Low	18"
NuQ 12 Biamp	**NuQ12_bi**	Biamp	2way	Hi	1.4"
				Low	12"
NuQ 12 Biamp + B18	**NuQ12_bi+B18**	Biamp+Sub	3way	Hi	1.4"
				Mid	12"
				Low	18"
NuQ 15 Passive	**NuQ15_pa**	Passive	1way		15" + 1.4"
NuQ 15 Passive + B18	**NuQ15_pa+B18**	Passive+Sub	2way	Hi	15" + 1.4"
				Low	18"
NuQ 15 Biamp	**NuQ15_bi**	Biamp	2way	Hi	1.4"
				Low	12"
NuQ 15 Biamp + B18	**NuQ15_bi+B18**	Biamp+Sub	3way	Hi	1.4"
				Mid	12"
				Low	18"

Flex array (TFA-600) series					
Note: Use as a combinanation of Input PEQ and cross-over. **Settings are for TSW218. For TFA600L, add +3dB.** **Settings are based on 26dB gain amplifiers.**					
Model	**File name**	**Mode**	**Module**		**Driver**
TFA-600H active+TSW218/TFA600L 4way cross-over **Use with PEQ**	**TFA600_4wyXovr**	4way	4way	Hi	1"
				Hi-Mid	6.5"
				Low-Mid	2 x 10"
				Low	2x18" / 18"
PEQ for a point source or near field applications for up to 3 enclosures	**TFA600_4wyPEQ1**	use with 4way Xovr	PEQ-Mono 8		-
PEQ for short to midfield systems from 3 to 6 enclosures	**TFA600_4wyPEQ2**				
PEQ for midfield to long throw systems from 6 to 8 enclosures	**TFA600_4wyPEQ3**				
PEQ for all long throw systems of 9 enclosures or over	**TFA600_4wyPEQ4**				
TFA-600H passive+TSW218/TFA600L 3way cross-over **Use with PEQ**	**TFA600_3wyXovr**	3way	3way	Hi	6.5"+1"
				Mid	2 x 10"
				Low	2x18" / 18"
PEQ for a point source or near field applications for up to 3 enclosures	**TFA600_3wyPEQ1**	use with 3way Xovr	PEQ-Mono 8		-
PEQ for short to midfield systems from 3 to 6 enclosures	**TFA600_3wyPEQ2**				
PEQ for midfield to long throw systems from 6 to 8 enclosures	**TFA600_3wyPEQ3**				
PEQ for all long throw systems of 9 enclosures or over	**TFA600_3wyPEQ4**				

Example